

# LSS



## DNP

Portable version of the digital auxiliary console with 8" LCD-touchscreen and customizable and programmable interface for the control of auxiliary functions in the theater- and event technology, like houselights, worklights and switchable circuits. This console is also available with 10,4" / 15,0" or 19,0" TFT display.

### Touchcomputer:

<b>Processor</b>	Mobile Intel Celeron 600 MHz
<b>Main memory (RAM)</b>	512 MB
<b>Copact Flash base</b>	4 GB
<b>Interfaces</b>	3x USB 2.0 Ports (internal) / 1x RS-232 serial ports (internal) 1x PS/2 Mouse + Keyboard/combi (internal)
<b>Network</b>	TCP/IP 10/100Base-T / RJ45 (Ethernet) internal
<b>Operating system</b>	Microsoft Windows XP Embedded

### Touchmonitor:

<b>Type of display</b>	Active matrix TFT LCD			
<b>Display size / Diagonal</b>	8,0" / 203mm	10,4" / 264mm	15,0" / 381mm	19,0" / 483mm
<b>Aspect ratio</b>	4 x 3	4 x 3	4 x 3	4 x 3
<b>Resolution</b>	640 x 480	800 x 600	1024 x 768	1280 x 1024
<b>Brightness</b>	400 cd/m <sup>2</sup>	350 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
<b>Colors</b>	16,2 million colors			
<b>Touchscreen</b>	analog-resistive			
<b>4 keys for system control</b>	3 programmable keys (F1... F3) key "service mode" for the adjustment of the display brightness			

### General:

<b>Dimensions installation housing</b>	W x H x D 300 x 300 x 120mm	W x H x D 400 x 400 x 120mm	W x H x D 500 x 500 x 210mm	W x H x D 600 x 600 x 210mm
<b>Power supply</b>	optional 230V AC/50 Hz or 24V DC 25%			
<b>Power dissipation</b>	25W max. typical			
<b>Operating temperature</b>	0 - 45 °C			
<b>Humidity</b>	10 - 90%, not-condensing			